



Issuing Date February 2, 2012

Revision date July 16 2013

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name Sierra Synthetic Blend TC-W3 Two-Stroke Engine Oil

Product Code(s) 18-9530-3, 18-9530-3R, 18-9530-4R, 18-9530-6, 18-9530-7

Recommended Use Two-stroke Engine Oil.

Company Sierra International
1 Sierra Place
Litchfield, IL 62056

Manufactured for: SeaStar Solutions

Company Emergency Phone Number (618) 542-5431

Emergency telephone number Chemtrec 1-800-424-9300

2. Hazards Identification

EMERGENCY OVERVIEW

The product contains no substances which at their given concentration are considered to be hazardous to health

appearance Amber colored liquid **Physical state** viscous liquid **Odor** Mild petroleum odor, Petroleum solvent

Potential health effects

Principle Routes of Exposure Skin contact, ingestion, inhalation or injection.

Acute toxicity

EYES

Can be irritating to eyes. If contact occurs, flush with water for 30 minutes. Get medical attention if eye irritation persists.

skin

Avoid excessive contact with skin. Always wash skin and soiled clothing with soap and water after exposure.

inhalation

Remove exposed person to fresh air if adverse effects are observed.

INGESTION

Do not induce vomiting. Get medical attention.

Chronic effects

Environmental hazard	Always use proper personal protective equipment for petroleum based products if a spill occurs. Quarantine affected area, prevent spill from entry into sewers and waterways. Pick up free and residual liquid for proper disposal and/or recycling. Always follow proper local, state, and federal guidelines for clean up and disposal for motor oil and other petroleum products.
-----------------------------	--

3. Composition/information on Ingredients

Common Name	Synthetic hydrocarbon lubricating fluid. Hydrocarbon Lubricating Fluid.
Chemical Family	Petroleum hydrocarbon mixture.

Chemical name	CAS-No	Weight %
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	35.1
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	33.83
Residual oils (petroleum), solvent refined	64742-01-4	5.28

4. First aid measures

General advice	No hazards which require special first aid measures.
Eye contact	Flush eyes for 30 minutes with water. Get medical attention if irritation persists.
Skin contact	Wash off immediately with soap and plenty of water.
inhalation	Move exposed persons to fresh air. Consult medical personal if breathing issues occur.
INGESTION	Do NOT induce vomiting. Consult a physician.

5. Fire-fighting measures

Flammable properties	Product has a flash point of 86C. Because of this flash point, this material is considered combustible.
flash point	101C
Suitable extinguishing media	Carbon dioxide (CO ₂). Dry chemical. Foam. Water can be used to keep surrounding materials cool.
Large Fires	Contact emergency personnel

Explosion data				
NFPA	Health hazard -	flammability -	stability -	Physical and Chemical Hazards -

6. Accidental release measures

Personal precautions	Avoid contact with the skin and the eyes. Eye protection or face shield should be used if material is used under conditions that increase the chances of splattering. Wash skin with soap and water if contact occurs. Launder soiled clothing. If spilled, take caution, as material can cause surfaces to become very slippery.
Methods for containment	Cover with earth, sand, or other non-combustible material followed with plastic sheets to minimize spreading or contact with rain.
Methods for cleaning up	Excess liquid material can be collected using a scoop or shovel and stored for recycling or disposal. Prevent material from entering drains or waterways.

7. Handling and Storage

Handling	Avoid contact with skin, eyes and clothing. Eye protection or face shield should be used if material is used under conditions that increase the chances of splattering. If contact is made, wash skin with soap and water. Launder soiled clothing. Maximum handling temperature is 70 degrees C (158 F). It is recommended to pump or transfer material at ambient temperature.
Storage	Keep away from heat and sources of ignition. Keep containers closed when not in use. Follow first aid measures if contact occurs, and spill procedures if spill occurs. For packaged material: Store in a cool dry area. For bulk material: store in cool dry area. Always follow local, state, and federal guidelines for storage of material for amount stored.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protective equipment	
Eye/face Protection	If splashes are likely to occur, wear:. Goggles. Eye/face Protection.
Skin and body protection	Long sleeved clothing. Protective gloves can be worn, if material comes in contact with skin wash with soap and water.
Hygiene Measures	Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

appearance	Amber colored liquid	Odor	Mild petroleum odor, Petroleum solvent
Physical state	viscous liquid		
flash point	101C	Autoignition temperature	No information available
Boiling Point/Range	No information available	Flammability Limits in Air	No information available
Explosion Limits	No information available		
solubility	No information available	evaporation rate	No information available
vapor pressure	No information available	vapor density	No information available
viscosity	Viscosity at 40C (ASTM D-445), cSt: 37.50 Viscosity at 100C (ASTM D-445), cSt: 6.69		

10. Stability and Reactivity

stability	Stable under normal conditions.
------------------	---------------------------------

11. Toxicological Information

Acute toxicity

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, hydrotreated heavy paraffinic	2000 mg/kg (Rat)	2000 mg/kg (Rabbit)	2.18 mg/L (Rat) 4 h
Petroleum distillates, solvent dewaxed heavy paraffinic	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	2.18 mg/L (Rat) 4 h
Residual oils (petroleum), solvent refined	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	2.18 mg/L (Rat) 4 h

Chronic toxicity

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, hydrotreated heavy paraffinic		Group 1		X
Petroleum distillates, solvent dewaxed heavy paraffinic		Group 1		X
Residual oils (petroleum), solvent refined		Group 1		X

12. Ecological Information

ecotoxicity

Chemical name	Toxicity to Algae	Toxicity to Fish	Microtox	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated heavy paraffinic		LC50> 5000 mg/L Pimephales promelas 96 h		EC50 > 1000 mg/L 48 h
Petroleum distillates, solvent dewaxed heavy paraffinic		LC50> 5000 mg/L Pimephales promelas 96 h		EC50 > 1000 mg/L 48 h
Residual oils (petroleum), solvent refined		LC50> 5000 mg/L Pimephales promelas 96 h		EC50 > 1000 mg/L 48 h

13. Disposal Considerations

14. Transport Information

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. Regulatory information

International Inventories

TSCA	Complies
DSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

Clean Water Act

CERCLA

U.S. State Regulations

Chemical name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Diphenylamine	X	X	X		X

International Regulations

Mexico - Grade No information available

CANADA

WHMIS Hazard Class

Not Determined

16. Other information

NFPA	HMIS	PPE	Transport Symbol
(Bad file name)	(Bad file name)		

Issuing Date

February 2, 2012

Revision date 16-Jul-2013

Revision note

No information available

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS