LOXX

Schæffertec

Produktdatenblatt / Technical Data Sheet

Schraube für Blech, Holz, Kunstoff/ Schlüsselweite 9mm; 100St/box
Screw metal, wood, plastic thread/ wrench size 9mm; 100pc/box



Artikel / item	Artikelnummer/ item code	Material & Oberfläche / material & surface	Ø D Gewinde Ø/ thread Ø mm	l_N Gewindelänge/ thread length mm	L_t Gesamthöhe/ total height mm	SW Schlüsselweite/ wrench size mm
Selbstschneidende Schraube* self-tapping screw*	05931.05098	brass / Stainless Steel thread nickel plated	ST 4,2	10	20,8	9
	05931.11000	brass / Stainless Steel thread chrome plated	ST 4,2	10	20,8	9
	05931.79098	brass / Stainless Steel thread black chrome plated	ST 4,2	10	20,8	9
	08857.00000	Stainless Steel	ST 4,2	10	20,8	9
	04386.05098	brass / Stainless Steel thread nickel plated	ST 4,2	12	22,8	9
	04386.11000	brass / Stainless Steel thread chrome plated	ST 4,2	12	22,8	9
	04386.79098	brass / Stainless Steel thread black chrome plated	ST 4,2	12	22,8	9
	08859.00000	Stainless Steel	ST 4,2	12	22,8	9
	07190.05098	brass / Stainless Steel thread nickel plated	ST 4,2	16	26,8	9
	07190.11000	brass / Stainless Steel thread chrome plated	ST 4,2	16	26,8	9
	07190.49000	brass / Stainless Steel thread gold plated	ST 4,2	16	26,8	9
	07190.79098	brass / Stainless Steel thread black chrome plated	ST 4,2	16	26,8	9
	08856.00000	Stainless Steel	ST 4,2	16	26,8	9
erh.Kopf high head	01590.05098	brass / stainless steel thread nickel plated	ST 4,2	16	28,9	9
erh.Kopf high head	01590.11000	brass/ stainless steel thread chrome plated	ST 4,2	16	28,9	9
	08003.05098	brass / stainless steel thread nickel plated	ST 4,2	22	32,7	9
	08003.11000	brass / stainless steel thread chrome plated	ST 4,2	22	32,7	9
	08003.79098	brass / stainless steel thread black chrome plated	ST 4,2	22	32,7	9
	08003.49000	brass / stainless steel thread gold plated	ST 4,2	22	32,7	9
	08573.05098	brass / stainless steel thread nickel plated	ST 4,2	26	36,7	9
	08573.11000	brass / stainless steel thread chrome plated	ST 4,2	26	36,7	9
	08004.05098	brass / stainless steel thread nickel plated	ST 4,8	12	22,8	9
	08004.11000	brass / stainless steel thread chrome plated	ST 4,8	12	22,8	9



Artikel / item	Artikelnummer/ item code	Material & Oberfläche / material & surface	Ø D Gewinde Ø/ thread Ø mm	l_N Gewindelänge/ thread length mm	L_t Gesamthöhe/ total height mm	SW Schlüsselweite/ wrench size mm
	08005.05098	brass / stainless steel thread nickel plated	ST 4,8	16	26,8	9
	08005.11000	brass / stainless steel thread chrome plated	ST 4,8	16	26,8	9
Holzschraube / wood screw extra lang / long	08843.00000	Stainless Steel A2 - DIN571	5	30	41,4	9
	08844.00000	Stainless Steel A2 - DIN571	5	35	46,4	9
	08845.00000	Stainless Steel A2 - DIN571	5	40	51,4	9
	08846.00000	Stainless Steel A2 - DIN571	5	45	56,4	9

* Blechschraubengewinde DIN EN ISO 1478

** Holzschraubengewinde nach DIN 571

* Vorbohren Ø 3,2mm für ST 4,2/ pre-drill Ø 3,2mm für ST 4,2

* Vorbohren Ø 3,4 - 3,7mm für ST 4,8/ pre-drill Ø 3,4 - 3,7mm für ST 4,8

* Vorbohren Ø 3,4 - 3,7mm für ST 4,8/ pre-drill Ø 3,4 - 3,7mm für ST 5

* Querkräfte 1.200 N/ lateral forces 122,4 kp
* Längskräfte1.200 N / axial forces 122,4 kp

Kombination mit LOXX Oberteilen
combined with LOXX upper parts

* Kombinierbar mit allen LOXX Oberteilen/ compatible with all LOXX upper parts

V2A-Schrauben Festigkeitsklasse 6.8 - Empfohlenes Anzugsmoment (Nm) 2,8

Srew STST V2A property class 6.8 - Specified bolting torque (Nm) 2,8