OSCULATI

Cutting compounds and Polish

Full range from professional to DIY uses



Heavy 1000 - Coarse-grained abrasive paste



◢65.220.10


◢65.230.16 (OPTIONAL)


◢65.230.01 (OPTIONAL)

Coarse-grained polishing abrasive paste to be used after sanding with P1000 grain.
Excellent abrasive capacity combined with high-polishing level.
For oxidized and yellowed gelcoat.

Code	Polisher speed	To be used with OPTIONAL		Package	PACKAGE
		rough woollen cover (strong action)	orange cover (lighter action)		
65.220.10	800 - 1500 rpm	**65.230.16**	**65.230.01**	1 kg	12

Medium 1500 - Medium-power abrasive paste



◢65.221.05/10


◢65.230.15 (OPTIONAL)


◢65.230.01 (OPTIONAL)

Medium-power polishing abrasive paste to be used after sanding with P1500 grain.
It removes streaks and oxidation for an extremely bright and smooth surface.
Suitable for soft and coloured gelcoat and painted surfaces.

Code	Polisher speed	To be used with OPTIONAL		Package	PACKAGE
		fine woollen cover (strong action)	orange cover (lighter action)		
65.221.05	800 - 1500 rpm	**65.230.15**	**65.230.01**	500 g	20
65.221.10	800 - 1500 rpm	**65.230.15**	**65.230.01**	1 kg	12

Light 2500 - Finishing polish



◢65.222.05/10


◢65.230.02 (OPTIONAL)

Finishing polish that removes polishing marks, micro-streaks and holograms.
The combination of nano-abrasive and polishing agents ensures bright surfaces in a matter of little time and effortlessly.
For dark delicate surfaces.

Code	Polisher speed	To be used with blue cover OPTIONAL	Package	PACKAGE
65.222.05	1000 - 2000 rpm	**65.230.02**	500 g	20
65.222.10	1000 - 2000 rpm	**65.230.02**	1 kg	12

Polish + Wax - Protective polish + wax



◢65.223.05/10


◢65.230.03 (OPTIONAL)


◢65.230.40 (OPTIONAL)

Protective polish + wax that removes light oxidation, water stains and little flaws for extremely bright surfaces.
This polymer composite combines the polishing action with the spreading of a highly protective and durable water-repellent layer against the action of UV rays, weather agents and salt/calcareous water.
It prevents opacity, stains and marks.
It can also be applied by hand and by machine.

Code	Polisher speed	To be used with OPTIONAL		Package	PACKAGE
		Black cover (by machine)	Microfibre cloth (by hand)		
65.223.05	1500 - 2000 rpm	**65.230.03**	**65.230.40**	500 g	20
65.223.10	1500 - 2000 rpm	**65.230.03**	**65.230.40**	1 kg	12

Heavy 600 - Coarse-grained abrasive paste for stain purposes


◢65.227.00


◢65.230.16 (OPTIONAL)


◢65.230.01 (OPTIONAL)

Polishing abrasive paste with high stain power, suitable after sanding with P600 sand paper.
Despite its high abrasive power, it doesn't generate streaks, marks or squirts.
It reduces the sanding cycles therefore it's ideal for works on rough hulls after repairs.
Also suitable for heavily oxidized gelcoat.

Code	Colour	Polisher speed	To be used with OPTIONAL		Package	PACKAGE
			rough woollen cover (strong action)	orange cover (lighter action)		
65.227.00	White	800 - 1500 rpm	**65.230.16**	**65.230.01**	3 kg	4
65.227.02*	Black	800 - 1500 rpm	**65.230.16**	**65.230.01**	3 kg	4

* *Ideal for dark colour hulls.*

Boat care accessories for OSCULATI abrasive pastes

Code	Description	To be used with	cm	PACKAGE
65.230.01	2 medium-stiff orange foam pads	**65.230.21/22**	Ø 15	20
65.230.02	2 medium-soft blue foam pads	**65.230.21/22**	Ø 15	20
65.230.03	2 soft black bubbly foam pads	**65.230.21/22**	Ø 15	20
65.230.15	Fine wool cover	**65.230.21**	Ø 20	20
65.230.16	Double-sided rough wool cover	**65.230.23**	Ø 26	10
65.230.21	Backing pad for drill	**65.230.01/02/03**	Ø 7.5	10
65.230.22	Hand-held backing pad	**65.230.01/02/03**	Ø 14.5	10
65.230.23	Adapter for rough wool cover	**65.230.16**	-	10
65.230.40	2 microfibre cloths	**-**	38x38	20


◢ 65.230.01



◢ 65.230.02


◢ 65.230.03


◢ 65.230.15


◢ 65.230.22


◢ 65.230.23


◢ 65.230.40


◢ 65.230.02


◢ 65.230.16


◢ 65.230.21

Cutting compounds and Polish

A wide range with packs from 0.5 kg to 3 kg,
ideal for small jobs, or professional shipyards.

- Excellent product coverage
- Developed for the marine environment
- Clear instructions, in four languages
- Match the lid colour to the tools





This fast cutting compound quickly removes scratches, defects and sanding marks

Osculati S.r.l.
Via Pacinotti, 12 - 20090 Segrate (MI)
Tel +39 02 2699 111 - info@osculati.it

Osculati & C. S.p.A.
Via di Sottopoggio - 55012 Capannori (LU)
Tel +39 0583 403 232 - info@lucca.osculati.it

Code 70.199.30-05EN

8 033137 194771

FSC
www.fsc.org
MISTO
Carta da fonti gestite in maniera responsabile
FSC® C120386