
❶ Il doppio giro di sfere in delrin® consente un elevato carico di lavoro distribuendo lo sforzo in modo uniforme.
❷ Il disegno delle ganasce facilita l'inserimento della scotta e ne previene la lacerazione grazie agli spigoli arrotondati.
• Le molle di torsione in acciaio inox (di nuovo disegno) sono state concepite per oltre 50.000 aperture.
• Si raccomanda di non serrare esageratamente le viti di fissaggio e di lavare periodicamente gli strozzascotte con acqua dolce.



❶ The cams are fitted with a double ring of delrin® balls and ensure a high working load by distributing the stress uniformly.
❷ The design of the cams eases the insertion of the rope and prevents the latter from being torn thanks to the rounded edges.
• The s/s springs are of a new conception and have been tested on more than 50.000 openings.
• Don't tighten the screws down too hard.
• Ball bearing cam cleats should be washed with fresh water regularly.

	MATERIALE / MATERIAL	DIAM. SCOTTA (min / max) LINE SIZE (min / max)	INTERASSE FORI HOLE SPACING	DIAM. FORI HOLES DIAMETER	PESO WEIGHT	CARICO MAX DI LAVORO MAX WORKING LOAD	DIMENSIONI OVERALL DIMENSIONS
25.10	Fibra di Carbonio	mm 3 / 8	mm 27	mm 4	gr 15	Kg 90	mm 47X23X20H
	Carbon fibre	1/8" - 5/16"	1 1/16"	5/32"			1 13/16" X 7/8" X 3/4" H
25.50	Base fibra di Carbonio Ganasce lega leggera	mm 3 / 8	mm 27	mm 4	gr 24	Kg 100	mm 47X23X20H
	Base carbon fibre Cams aluminium	1/8" - 5/16"	1 1/16"	5/32"			1 13/16" X 7/8" X 3/4" H
25.30	Lega leggera	mm 6 / 14	mm 38	mm 5	gr 66	Kg 140	mm 64X30X28H
	Aluminium	1/4" - 9/16"	1 1/2"	3/16"			2 1/2" X 1 3/16" X 1 1/16" H
25.32	Fibra di Carbonio	mm 6 / 14	mm 38	mm 5	gr 36	Kg 110	mm 64X30X28H
	Carbon fibre	1/4" - 9/16"	1 1/2"	3/16"			2 1/2" X 1 3/16" X 1 1/16" H



Le guide posteriori e superiori sono realizzate in materiale composito anti-abrasione.

The front and top fairleads are made from tough, abrasion resistant composite material.

Per 25.10 25.50		Ponticello superiore	35.18	*Top mount*	For 25.10 25.50
		Ponticello anteriore	25.12	*Fairlead*	
		Basetta inclinata	25.13	*Angled base*	
		Guida posteriore	25.14	*Front mounted fairlead*	
	Nera	Guida superiore	25.15	*Top fairlead* **Black**	
	Rossa	Guida superiore	25.16	*Top fairlead* **Red**	
	Gialla	Guida superiore	25.17	*Top fairlead* **Yellow**	
	Blu	Guida superiore	25.18	*Top fairlead* **Blue**	
Per 25.30 25.32		Ponticello superiore	35.07	*Top mount*	For 25.30 25.32
		Basetta inclinata	25.40	*Angled base*	
		Basetta piana (indispensabile per il montaggio art 25.42)	25.41	*Parallel base (necessary for assembly of art. 25.42)*	
		Ponticello anteriore (altezza interna 37 mm)	25.42	*Fairlead (1 29/64" - Internal height)*	
		Ponticello anteriore basso (altezza interna 29 mm)	25.43	*Short fairlead (1 5/32" - Internal height)*	
		Guida posteriore	25.44	*Front mounted fairlead*	
	Nera	Guida superiore	25.45	*Top fairlead* **Black**	
	Rossa	Guida superiore	25.46	*Top fairlead* **Red**	
	Gialla	Guida superiore	25.47	*Top fairlead* **Yellow**	
	Blu	Guida superiore	25.48	*Top fairlead* **Blue**	



WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT
INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT