		DIAMETRO PULEGGIA SHEAVE DIAM.	CARICO DI ROTTURA BREAKING LOAD	MAX DIAM. SCOTTA MAX LINE DIAM.	
Realizzati in alluminio anodizzato duro a spessore + PTFE Fori Ø mm 6 Interasse fori mm 44	Rinvio piano a due pulegge su sfere in delrin®	mm 38 1 1/2"	15.45 Kg 800	mm 10 3/8"	*Ball bearing double sheave organiser (delrin® balls)*
	Rinvio piano a tre pulegge su sfere in delrin®	mm 38 1 1/2"	15.46 Kg 900	mm 10 3/8"	*Ball bearing triple sheave organiser (delrin® balls)*
	Rinvio piano a quattro pulegge su sfere in delrin®	mm 38 1 1/2"	15.47 Kg 1.000	mm 10 3/8"	*Ball bearing quadruple sheave organiser (delrin® balls)*
Fori Ø mm 6 Interasse fori mm 53	Rinvio piano a due pulegge su sfere inox	mm 44 1 3/4"	15.55 Kg 1.200	mm 14 9/16"	*Ball bearing double sheave organiser (inox balls)*
	Rinvio piano a tre pulegge su sfere inox	mm 44 1 3/4"	15.56 Kg 1.300	mm 14 9/16"	*Ball bearing triple sheave organiser (inox balls)*
	Rinvio piano a quattro pulegge su sfere inox	mm 44 1 3/4"	15.57 Kg 1.400	mm 14 9/16"	*Ball bearing quadruple sheave organiser (inox balls)*

Manufactured from hardcote + PTFE anodised aluminium

Holes diameter 1/4"

Holes spacing 1 47/64"

Holes diameter 1/4"

Holes spacing 2 3/32"



RINVII PIANI
ORGANISERS

PASSASCOTTE IN NYLON
FAIRLEADS & BULLSEYES

INTERASSE FORI mm	DIAM. FORI mm	MAX DIAM. SCOTTA mm		MAX ROPE DIAM. IN.	HOLES DIAM. IN.	HOLES SPACING IN.
42	5	14	36.01	9/16	3/16	1 5/8
33	5	12	36.02	7/16	3/16	1 1/4
26	4	8	36.03	5/16	5/32	1
19	3	6	36.04	1/4	1/8	3/4
37	5	14	36.05	9/16	3/16	1 7/16
37	5	12	36.06	7/16	3/16	1 7/16
32	5	10	36.09	3/8	3/16	1 1/4
22	4	6	36.10	1/4	5/32	7/8

Con boccola in acciaio inox *With stainless steel insert*



WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT
INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT